

# SKG certificate

## 527.313.01



### Certificate holder

Cisa SpA  
Via Oberdan 42  
IT-48018 Faenza Italie  
T: +39 (0) 546 677 111  
E: [cisa@eu.irco.com](mailto:cisa@eu.irco.com)  
I: [www.cisa.ingersollrand.com](http://www.cisa.ingersollrand.com)

### Address

Nieuwe Kanaal 9F  
Wageningen  
Postadres  
Postbus 362  
6700 AJ Wageningen  
T 0317 – 421 720  
F 0317 – 421 677  
E [info@skg.nl](mailto:info@skg.nl)  
I [www.skg.nl](http://www.skg.nl)



date of issue: 6-feb-2013

Verify at [www.sterrenwijzer.nl](http://www.sterrenwijzer.nl) if this  
certificate is still valid and actual

### Declaration of SKG:

SKG declares that the by or on behalf of the certificate owner produced building hardware product:

### euro profile cylinder

delivered under logo or brand:

**CISA**

delivered under type- and / or article number:

**RS3 S MODULO series: 1-OL3M1-xx-O-xx-xx-xx**

**meets class 3 STAR according BRL 3104: 2012-08-21 and NEN 5089: 2009**

if the product is indelibly marked with the SKG security mark, as shown aside.



Wageningen, 6-feb-2013

ir. H.A.J. van Dartel  
certification manager

This certificate is in accordance with the SKG Regulations approval, product certification and process certification: 2011.

### Validity of this certificate:

This product certificate is valid in so far as all the obligations bound herewith are met and in so far as the period of validity has, for whatever reason, not been terminated at an earlier date.

Validity is cancelled in any case when:

- the certificate agreement is discontinued;
- this certificate is withdrawn;
- this certificate is issued on a more recent date.



# SKG certificate

Security building hardware product of Cisa SpA

Number: 527.313.01 date of issue: 6-feb-2013

## 1. PRODUCT

euro profile cylinder

Main group

cylinder

## 2. TECHNICAL SPECIFICATION:

Construction: modular system single parts

Operating / System: vertical key profile; 1 row of 5 + 2 rows of 4/2 + 2 mechanical operated retainers

Material: cylinder body: brass with various coatings

Dimension: 17 mm profile from 30 mm in various extensions per 5 mm

Fixing: 1 steel bolt M5

Intended use: in combination with cylinder mortice locks and security furniture

## 3. CLASSIFICATION according European standard: EN 1303

| digit | 1 | 2 | 3 | 4 | 5 | 6 | 7 | 8 |
|-------|---|---|---|---|---|---|---|---|
| grade | 1 | 6 | 0 | 0 | 0 | A | 6 | 2 |

for explanation digits see: EN 1303

## 4. DELIVERY

The delivery includes an installation instruction:

0.892.0341.0.00.00/A

## 5. PERFORMANCES

A cylinder according this certificate fulfills the relevant requirements of BRL 3104: 2012-08-21 and NEN 5089: 2009.

A door or window, in which a euro profile cylinder is installed according the installation instructions of the certificate holder meets at least RC 2 of NEN 5096 / EN 1627 if:

Wooden doors or windows are produced and delivered under KOMO-attest met Productcertificaat and meets the requirements of publication 98-08 of SKH, including the herein mentioned limiting conditions.

The (profile-)system from which metal or PVC doors or windows are produced is delivered under a SKG-KOMO systemattest burglar resistance, in which the actual type of door or window is admitted and the herein mentioned conditions are fulfilled

Remark: Only 3-star cylinders are applicable in a RC of EN 1627